

PAJ のり

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 02-294574

(43)Date of publication of application : 05.12.1990

(51)Int.Cl.

F04B 37/16

F04C 25/02

F04D 19/04

(21)Application number : 01-114954 (71)Applicant : HITACHI LTD


(22)Date of filing : 10.05.1989 (72)Inventor : UCHIDA RIICHI

(54) VACUUM EXHAUST DEVICE

(57)Abstract:

PURPOSE: To perform baking of a vacuum device without using a heater and to reduce an ultimate pressure by providing a means to guide a compression heat, generated at a pump at a subsequent stage, to a pump at a preceding stage.

CONSTITUTION: Since sucked gas is compressed to an atmospheric pressure with the aid of a screw vacuum pump 1, the temperature of a working chamber is increased to approximate 200-400° C. Heat the temperature of which is increased to a high value passes through the inner wall of a main casing 4 to heat circulating water in a heat receiving jacket 13. Circulating water the temperature of which is increased to a high value is guided through a conduit 29 to a heating jacket 28 and heats a casing 22 of a screw groove molecular pump 2, and further heats a screw groove rotor 21. As a result, separation of a gas molecule adsorbed to the inside of the screw groove molecular pump 2 is promoted, and the pressure of a vacuum device can be easily reduced. Since heating degassing operation of the vacuum device, so-called baking, is effected by means of the compression heat of the pump itself, a heater and source equipment can be eliminated.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision
of rejection]